

# NSA CARBON ARMOUR Coverall



## Specs

Product Code	SPXHPCA0208_ _ _ _
Sizes	MD-3X, RG
Stock Colors	
Fabric / Material	OPF Blend Twill

# Compliance

Arc Rating	9 cal/cm²
CAT Level	CAT 2
Standards	<ul style="list-style-type: none"><li>• NFPA 70E</li><li>• ASTM F1506</li><li>• CSA Z462</li><li>• OSHA 1910.269</li><li>• Anti-Static per EN 1149-5</li><li>• EN ISO 11611 A1, Class 2; A2, Class 2; 6.8 impact of spatter, Class 2; 6.9 heat transfer (radiation), Class 1</li></ul>

# Features

Features	<ul style="list-style-type: none"><li>• Exceptional tensile and tear strength</li><li>• Moisture wicking and fast drying</li><li>• Excellent comfort and durable protection</li><li>• Two chest pockets with flaps and snap closure</li><li>• Action back for increased movement</li><li>• Inset elastic waistband</li><li>• Covered FR zip front closure with additional snaps</li><li>• FR fabric will not melt, drip, or ignite</li><li>• Inherently flame resistant, FR protection will not wash/wear out</li><li>• Anti-static fabric meets requirements for shielding factor and half decay time</li><li>• Made in the USA</li></ul>
----------	--

# Product Care

Product Care	<ul style="list-style-type: none"><li>• READ THE GARMENT LABEL AND LAUNDER PER INSTRUCTIONS ON GARMENT LABEL.</li><li>• DO NOT use bleach, chlorine, or hydrogen peroxide. DO NOT use fabric softeners.</li><li>• Turn garment inside out prior to laundering Machine wash cold with like colors (Max. 105°F / 41°C) Tumble dry low (Max. 140°F / 60°C).</li><li>• Wash according to the instructions above to remove any contaminants in order to maintain fabric performance when garment becomes soiled with dirt, greases, oils, etc.</li><li>• If contaminants cannot be removed after laundering, it is best to discontinue use of garment.</li></ul>
--------------	---

