

DRIFIRE HYDROflash FR Hi-Vis Rain Hood





Specs

Product Code	• HYDROFLASHH-Y (Yellow) • HYDROFLASHH-O (Orange)
Sizes	One Size Fits Most
Stock Colors	
Made To Order Colors	
Fabric / Material	GORE-TEX PYRAD® Polyester on ePTFE

Compliance

Arc Rating	30 cal/cm ²
CAT Level	CAT 3
ANSI Type / Class	Type R Class 3
Standards	• ASTM F2733 • ASTM F1891 • CSA Z462 • ASTM F903 • OSHA 1910.269 • Gas Probe Shirley Method 138:2000, EN 1149-3/2004 & EN 1149-5/2008

Features

 HYDROFlash FR™ (2 Layer PYRAD) is the lightest weight waterproof, breathable Flash Fire rated garment available Lightweight, breathable, and fast drying 100% waterproof and windproof Resists cold cracking in low temperatures Hot liquid and steam resistant Petroleum and oil-based mud resistant Detachable, snap-on jacket hood is sold separately Hook and loop adjustment for secure fit Field repair kit is available (sold separately) Made in the USA

Product Care	 READ THE GARMENT LABEL AND LAUNDER PER INSTRUCTIONS ON GARMENT LABEL. DO NOT use bleach or hydrogen peroxide. DO NOT use fabric softeners. Wash/Laundering Instructions: Wash separately from other garments. Machine wash warm (max. 120°F/50°C) using mild detergent. Rinse 4 times (adding extra rinse to standard 3-rinse cycle) to remove all soil and detergent residues. Dawn Dish Liquid is recommended for oil based stains. Pre-treat the area, soak for stubborn stains or mild stain treatments may be used. Ensure the product is completely rinsed from the fabric before drying.
	 Drying: Turn garment inside out before drying. Tumble dry using permanent press setting (medium). Tumble drying is recommended to protect garment's water repellent treatment. Wash according to the instructions above to remove any contaminants in order to maintain fabric performance when garment becomes soiled with dirt, greases, oils, etc. If contaminants cannot be removed after laundering, it is best to discontinue use of garment.

