


DRIFIRE HYDROflash FR Rain Hood



Specs

Product Code	HYDROFLASHH-N
Sizes	One Size Fits Most
Stock Colors	
Fabric / Material	GORE-TEX PYRAD® Polyester on ePTFE

Compliance

Arc Rating	30 cal/cm²
CAT Level	CAT 3
Standards	<ul style="list-style-type: none">• ASTM F2733• ASTM F1891• CSA Z462• ASTM F903• OSHA 1910.269• Gas Probe Shirley Method 138:2000, EN 1149-3/2004 & EN 1149-5/2008

Features

Features	<ul style="list-style-type: none">• HYDROFlash FR™ (2 Layer PYRAD) is the lightest weight waterproof, breathable Flash Fire rated garment available• Lightweight, breathable, and fast drying• 100% waterproof and windproof• Resists cold cracking in low temperatures• Hot liquid and steam resistant• Petroleum and oil-based mud resistant• Detachable, snap-on jacket hood is sold separately• Hook and loop adjustment for secure fit• Field repair kit is available (sold separately)• Made in the USA
----------	--

Product Care

Product Care

- READ THE GARMENT LABEL AND LAUNDRER PER INSTRUCTIONS ON GARMENT LABEL.
- DO NOT use bleach or hydrogen peroxide. DO NOT use fabric softeners.
- Wash/Laundering Instructions: Wash separately from other garments. Machine wash warm (max. 120°F/50°C) using mild detergent. Rinse 4 times (adding extra rinse to standard 3-rinse cycle) to remove all soil and detergent residues. Dawn Dish Liquid is recommended for oil based stains. Pre-treat the area, soak for stubborn stains or mild stain treatments may be used. Ensure the product is completely rinsed from the fabric before drying.
- Drying: Turn garment inside out before drying. Tumble dry using permanent press setting (medium). Tumble drying is recommended to protect garment's water repellent treatment.
- Wash according to the instructions above to remove any contaminants in order to maintain fabric performance when garment becomes soiled with dirt, greases, oils, etc.
- If contaminants cannot be removed after laundering, it is best to discontinue use of garment.

